

1/17

Freitag März 10, 2006

```

195     CALL print_vec2d('x',x,m,n)
196   END IF
197
198   IF (my_rank==0) THEN
199     WRITE(*,'(A,I5,A,E8.2,A,E8.2)') 'main: ', num_iter, ' iterations, sqrt(eps)= ', SQRT(epsilon), &
200       & ' , normalized: ', SQRT(epsilon/(n*m))
201     WRITE(*,'(A,E8.2,A,E8.2)') 'main: ||r|| = ', norm_r, ' , normalized: ', norm_r/SQRT(REAL (n*m))
202     WRITE(*,'(A,E8.2,A,E8.2)') 'main: ||error||= ', norm_err, ' , normalized: ', norm_err/SQRT(REAL (n*m))
203     WRITE(*,'(A,E8.2,A,E8.2)') 'main: max(error)= ', maxnorm_err, ' = normalized: ', maxnorm_err
204     WRITE(*,'(A,I,A,I,A,I)') 'main: n*m= ', n, ' * ', m, '= ', n*m
205     WRITE(*,'(A,E8.2,A)') 'main: ', time_elapsed_cpu, ' sec (exec. time CPU_TIME)'
206   #ifndef serial
207     WRITE(*,'(A,E8.2,A)') 'main: ', time_elapsed, ' sec (exec. time MPI_WTIME)'
208     WRITE(*,'(A,E8.2,A)') 'main: ', commtime_sum, ' sec (comm. time)'
209     percentage = commtime_sum * 100.0 / time_elapsed
210     WRITE(*,'(A,I2,A)') 'main: ratio (comm. time)/(exec. time): ', percentage, '%'
211   #endif
212   WRITE(*,'(A,F8.2)') 'Calculated MFLOPS (avg) CPU_TIME: ', global_mflops_cpu / numprocs
213   WRITE(*,'(A,F8.2)') 'Calculated MFLOPS (all) CPU_TIME: ', global_mflops_cpu
214   #ifndef serial
215     WRITE(*,'(A,F8.2)') 'Calculated MFLOPS (avg) MPI_WTIME: ', global_mflops / numprocs
216     WRITE(*,'(A,F8.2)') 'Calculated MFLOPS (all) MPI_WTIME: ', global_mflops
217   #endif
218   END IF
219
220   IF (print_level>=1) THEN
221     CALL print_vec2d('x',x,mprr,nprtr)
222   END IF
223
224   #ifndef serial
225     CALL MPI_FINALIZE(ierr)
226   #endif
227
228   ! beginning of the subroutine part
229   CONTAINS
230
231   ! ***** memory management *****
232
233   SUBROUTINE abrt
234   #ifndef serial
235     CALL MPI_ABORT(MPI_COMM_WORLD, -1, ierr)
236   #endif
237   STOP
238   END SUBROUTINE abrt
239
240   ! ***** commandline options *****
241
242   SUBROUTINE read_options()
243     INTEGER :: optid = 1 ! start at first optional argument
244     INTEGER :: argc
245     LOGICAL :: err_detected = .FALSE.
246     CHARACTER(len=255) :: arg
247     argc = iargc()
248     IF ( my_rank == 0 ) THEN
249       DO WHILE( optid <= argc )
250         CALL getarg(optid, arg)
251         IF (arg == '-m') THEN
252           optid = optid + 1
253           CALL getarg(optid, arg)
254           READ (arg, *) m
255           IF (m<=0) THEN
256             err_detected = .TRUE.
257             EXIT
258           END IF
259         ELSE IF (arg == '-n') THEN
260           optid = optid + 1
261           CALL getarg(optid, arg)
262           READ (arg, *) n
263           IF (n<=0) THEN
264             err_detected = .TRUE.
265             EXIT
266           ENDIF
267         ELSE IF (arg == '-imax') THEN
268           optid = optid + 1
269           CALL getarg(optid, arg)
270           READ (arg, *) iter_max
271           IF (iter_max<=0) THEN
272             err_detected = .TRUE.
273             EXIT
274           ENDIF
275         ELSE IF (arg == '-eps') THEN
276           optid = optid + 1
277           CALL getarg(optid, arg)
278           READ (arg, *) epsilon
279           IF (epsilon<=0) THEN
280             err_detected = .TRUE.
281             EXIT
282           END IF
283         ELSE IF (arg == '-prtlev') THEN
284           optid = optid + 1
285           CALL getarg(optid, arg)
286           READ (arg, *) print_level
287           IF (print_level<0) THEN
288             err_detected = .TRUE.
289             EXIT
290           END IF
291         ELSE IF (arg == '-twodims') THEN

```

Freitag März 10, 2006

5/17

Freitag März 10, 2006

7/17

```

604 !-----
605 ! comm_vec_halo
606 !
607 ! IN REAL(0:) v1: the vector with the data to send to other processes
608 !
609 ! TASK:
610 !   Send neccessary data to the neighbors
611 !   and receive the needed data from the neighbors into
612 !   the halo area.
613 !
614 ! USED GLOBAL DATA:
615 !   IN/OUT halo_structure halo : the halo
616 !   IN   INTEGER rowsize : number of data entries in a row of the local chunk
617 !   IN   INTEGER colsize : number of data entries in a column of the local chunk
618 !   OUT REAL(0:) recv_scratch_buff_north : receive buffer for north halo
619 !   OUT REAL(0:) recv_scratch_buff_east  : receive buffer for east halo
620 !   OUT REAL(0:) recv_scratch_buff_south : receive buffer for south halo
621 !   OUT REAL(0:) recv_scratch_buff_west  : receive buffer for west halo
622 !
623 ! USED FUNCTIONS:
624 !   MPI:
625 !     MPI_IRECV, MPI_SEND, MPI_WAITALL
626 !
627 ! message tags for the different communication directions
628 SUBROUTINE comm_vec_halo(v1)
629   REAL, DIMENSION(0:), INTENT(IN), TARGET :: v1
630   INTEGER :: i
631
632   INTEGER :: req_array(4)
633   INTEGER :: status_array(MPI_STATUS_SIZE, 4)
634   INTEGER :: TAG_FROM_NORTH_TO_SOUTH = 101
635   INTEGER :: TAG_FROM_EAST_TO_WEST  = 102
636   INTEGER :: TAG_FROM_SOUTH_TO_NORTH = 103
637   INTEGER :: TAG_FROM_WEST_TO_EAST   = 104
638
639   REAL, DIMENSION(:), POINTER :: send_to_east_values
640   REAL, DIMENSION(:), POINTER :: send_to_west_values
641   REAL, DIMENSION(:), POINTER :: send_to_north_values
642   REAL, DIMENSION(:), POINTER :: send_to_south_values
643
644   ! make a non-blocking receive
645
646   ! Receive halo (non blocking). If current rank has no neighbors,
647   ! the neighbor rank is MPI_PROC_NULL and nothing is sent.
648
649   ! ATTENTION:
650   ! It is NOT allowed to use pointers or strided arrays in NON-blocking send/receive routines,
651   ! because the memory MAY NOT be contiguous. One must use a contiguous scratch buffer
652   ! for sending and receiving, if the memory is not contiguous or a pointer to an array.
653
654   ! receive north halo
655   CALL MPI_IRECV(recv_scratch_buff_north, halo%north_size, MPI_REAL, halo%north_rank, &
656     & TAG_FROM_NORTH_TO_SOUTH, comm_cart, req_array(1), ierror)
657   ! receive east halo
658   !02!CALL MPI_IRECV(recv_scratch_buff_east, halo%east_size, MPI_REAL, halo%east_rank, &
659   !02!   & TAG_FROM_EAST_TO_WEST, comm_cart, req_array(2), ierror)
660   ! receive south halo
661   !02!CALL MPI_IRECV(recv_scratch_buff_south, halo%south_size, MPI_REAL, halo%south_rank, &
662   !02!   & TAG_FROM_SOUTH_TO_NORTH, comm_cart, req_array(3), ierror)
663   ! receive west halo
664   !02!CALL MPI_IRECV(recv_scratch_buff_west, halo%west_size, MPI_REAL, halo%west_rank, &
665   !02!   & TAG_FROM_WEST_TO_EAST, comm_cart, req_array(4), ierror)
666
667   ! send to north neighbor (blocking)
668   send_to_north_values => v1(SIDX(1, 1):SIDX(colsize, 1):1)
669   CALL MPI_SEND(send_to_north_values, halo%north_size, MPI_REAL, halo%north_rank, &
670     & TAG_FROM_SOUTH_TO_NORTH, comm_cart, ierror)
671
672   ! send to east neighbor (blocking)
673   !02!send_to_east_values => v1(SIDX(1, rowsize):SIDX(colsize, rowsize):rowsize+2)
674   !02!CALL MPI_SEND(send_to_east_values, halo%east_size, MPI_REAL, halo%east_rank, &
675   !02!   & TAG_FROM_WEST_TO_EAST, comm_cart, ierror)
676
677   ! send to south neighbor (blocking)
678   !02!send_to_south_values => v1(SIDX(colsize, 1):SIDX(colsize, rowsize):1)
679   !02!CALL MPI_SEND(send_to_south_values, halo%south_size, MPI_REAL, halo%south_rank, &
680   !02!   & TAG_FROM_NORTH_TO_SOUTH, comm_cart, ierror)
681
682   ! send to west neighbor (blocking)
683   !02!send_to_west_values => v1(SIDX(1, 1):SIDX(colsize, 1):rowsize+2)
684   !02!CALL MPI_SEND(send_to_west_values, halo%west_size, MPI_REAL, halo%west_rank, &
685   !02!   & TAG_FROM_EAST_TO_WEST, comm_cart, ierror)
686
687   ! wait for all halo info
688   !02!CALL MPI_WAITALL(4, req_array, status_array, ierror)
689
690   ! copy the received halo from the scratch buff into the real halo
691   ! ATTENTION: pointers always start with the index 1!!!
692   IF (halo%north_rank /= MPI_PROC_NULL) THEN
693     DO i = 0, halo%north_size - 1
694       halo%north(i+1) = recv_scratch_buff_north(i)
695     END DO
696   END IF
697   !02!IF (halo%east_rank /= MPI_PROC_NULL) THEN
698   !02!   DO i = 0, halo%east_size - 1
699   !02!     halo%east(i+1) = recv_scratch_buff_east(i)
700   !02!   END DO

```


9/17

Freitag März 10, 2006

```

888 !-----
889 ! Init_2dim
890 !
891 ! TASK:
892 !   Do the two dimensional domain decomposition as depicted above.
893 !
894 ! USED GLOBAL DATA:
895 !   OUT INTEGER start_i      : start row of the physical area this process is to calculate
896 !   OUT INTEGER endl_i      : end row + 1 of the physical area this process is to calculate
897 !   OUT INTEGER start_j      : start column of the physical area this process is to calculate
898 !   OUT INTEGER endl_j      : end column + 1 of the physical area this process is to calculate
899 !   IN  INTEGER my_rank      : the rank of the current process
900 !   IN  INTEGER m_procs      : vertical number of processors
901 !   IN  INTEGER n_procs      : horizontal number of processors
902 !   OUT INTEGER comm_cart    : cartesian communicator
903 !   IN  INTEGER m            : vertical size of the physical problem
904 !   IN  INTEGER n            : horizontal size of the physical problem
905 !
906 ! USED FUNCTIONS:
907 !   APPL:
908 !     abrt
909 !   MPI:
910 !     MPI_CART_CREATE, MPI_COMM_RANK
911 SUBROUTINE Init_2dim()
912   INTEGER :: blocksize_i, blocksize_j
913   INTEGER :: startblock_i, startblock_j
914 #ifndef serial
915   INTEGER :: dims(0:1)
916   LOGICAL :: periods(0:1)
917   IF ((print_level >= 1) .AND. (my_rank == 0)) THEN
918     WRITE(*, '(A, I3, A, I3, A, I3)') 'Using 2-dim domain decomposition, m_procs=', m_procs, ', &
919       & n_procs=', n_procs, ', numprocs=', numprocs
920   END IF
921   ! Init the virtual topology (2-dims)
922   dims(0) = m_procs
923   dims(1) = n_procs
924   periods(0) = .FALSE.
925   periods(1) = .FALSE.
926 !04!_____
927 !04!_____
928 #endif
929
930   IF ((my_rank == 0) .AND. ((m_procs * n_procs) /= numprocs)) THEN
931     WRITE(*,*) 'Number of processors does not fit! Use ', (m_procs * n_procs), ' processors instead. &
932       & Aborting...'
933     CALL abrt()
934   END IF
935
936   ! the number of rows for each block (the last block might have
937   ! less than the first blocks)
938 !04!_____
939
940   ! the number of columns for each block (the last block might have
941   ! less than the first blocks)
942 !04!_____
943
944   ! calculate the start and end row and column
945 !04!_____
946 !04!_____
947 !04!_____
948 !04!_____
949 !04!_____
950 !04!_____
951 !04!_____
952 !04!_____
953 !04!_____
954 !04!_____
955 !04!_____
956 !04!_____
957 END SUBROUTINE Init_2dim
958
959 !-----
960 ! Init-Decomp
961 !
962 ! TASK:
963 !   Do the domain decomposition.
964 !
965 ! USED GLOBAL DATA:
966 !   IN/OUT INTEGER rowsize    : number of data entries in a row of the local chunk
967 !   IN/OUT INTEGER colsize    : number of data entries in a column of the local chunk
968 !   IN/OUT INTEGER chunksize  : number of data entries in the local chunk PLUS halo data
969 !   IN  INTEGER decomp_dims   : dimension of the domain decomposition
970 !   IN  INTEGER my_rank       : the rank of the current process
971 !
972 ! USED FUNCTIONS:
973 !   APPL:
974 !     abrt, Init_1dim, Init_2dim
975 SUBROUTINE Init-Decomp()
976   SELECT CASE (decomp_dims)
977     CASE (1)
978       CALL Init_1dim()
979     CASE (2)
980       CALL Init_2dim()
981     CASE DEFAULT
982       WRITE(*,*) 'Wrong decomp_dims=', decomp_dims
983       CALL abrt()
984   END SELECT

```

Freitag März 10, 2006

13/17

```

1176     WRITE(*,*) 'values: ', halo%west_size, ', neighbor rank: ', halo%west_rank
1177     DO i = 1, halo%west_size
1178         WRITE(*,*) 'halo[', i, ']: ', halo%west(i)
1179     END DO
1180 END IF
1181 WRITE(*,*) ''
1182 CALL flush_and_send_token()
1183 #endif
1184 END SUBROUTINE print_halo
1185
1186 SUBROUTINE print_halo_struct()
1187 #ifndef serial
1188     CALL recv_token()
1189
1190     WRITE(*,*) ''
1191     WRITE(*,*) 'Halo of rank ', my_rank
1192     WRITE(*,*) '-----'
1193     IF (halo%north_rank == MPI_PROC_NULL) THEN
1194         WRITE(*,*) 'North: NO halo'
1195     ELSE
1196         WRITE(*,*) 'North: values: ', halo%north_size, ', neighbor rank: ', halo%north_rank
1197     END IF
1198     IF (halo%east_rank == MPI_PROC_NULL) THEN
1199         WRITE(*,*) 'East: NO halo'
1200     ELSE
1201         WRITE(*,*) 'East: values: ', halo%east_size, ', neighbor rank: ', halo%east_rank
1202     END IF
1203     IF (halo%south_rank == MPI_PROC_NULL) THEN
1204         WRITE(*,*) 'South: NO halo'
1205     ELSE
1206         WRITE(*,*) 'South: values: ', halo%south_size, ', neighbor rank: ', halo%south_rank
1207     END IF
1208     IF (halo%west_rank == MPI_PROC_NULL) THEN
1209         WRITE(*,*) 'West: NO halo'
1210     ELSE
1211         WRITE(*,*) 'West: values: ', halo%west_size, ', neighbor rank: ', halo%west_rank
1212     END IF
1213     WRITE(*,*) ''
1214
1215     CALL flush_and_send_token()
1216 #endif
1217 END SUBROUTINE print_halo_struct
1218
1219 SUBROUTINE print_vec2d(name, v2, mprint, nprint)
1220 CHARACTER, INTENT(IN) :: name
1221 REAL, DIMENSION(0:), INTENT(IN) :: v2
1222 INTEGER, INTENT(IN) :: mprint, nprint
1223 INTEGER :: i, j
1224 REAL :: whole_v2(0:m-1, 0:n-1)
1225 #ifndef serial
1226     INTEGER :: rank
1227     REAL :: buff(0:(n + 2) * (m + 2) - 1)
1228     INTEGER :: extent(0:3), new_offset
1229     INTEGER :: status(MPI_STATUS_SIZE), status2(MPI_STATUS_SIZE)
1230
1231     IF (my_rank > 0) THEN
1232         ! send the start_i, endl_i, start_j, endl_j
1233         extent(0) = start_i
1234         extent(1) = endl_i
1235         extent(2) = start_j
1236         extent(3) = endl_j
1237         CALL MPI_SEND(extent, 4, MPI_INTEGER, 0, 666, comm_cart, ierror)
1238
1239         ! send the vector data to rank 0
1240         CALL MPI_SEND(v2, chunksize, MPI_REAL, 0, 333, comm_cart, ierror)
1241     ELSE
1242         ! copy the rank 0 chunk into the whole physical vector
1243         DO i = start_i, endl_i - 1
1244             DO j = start_j, endl_j - 1
1245                 whole_v2(i, j) = v2(SIDX((i - start_i + 1), (j - start_j + 1)))
1246             END DO
1247         END DO
1248
1249         ! receive the halo data and data extent from all other ranks into the buffer
1250         ! and copy the buffer to where it belongs into the whole physical vector
1251         DO rank = 1, numprocs - 1
1252             CALL MPI_RECV(extent, 4, MPI_INTEGER, rank, 666, comm_cart, status, ierror)
1253             CALL MPI_RECV(buff, ((extent(1) - extent(0) + 2) * (extent(3) - extent(2) + 2)), MPI_REAL, &
1254                 & rank, 333, comm_cart, status2, ierror)
1255
1256             new_offset = extent(3) - extent(2) + 2
1257
1258             DO i = extent(0), extent(1) - 1
1259                 DO j = extent(2), extent(3) - 1
1260                     whole_v2(i, j) = buff((i - extent(0) + 1) * new_offset + (j - extent(2) + 1))
1261                 END DO
1262             END DO
1263         END DO
1264     END IF
1265
1266     CALL appl_print_vec(name, whole_v2, mprint, nprint)
1267 #endif
1268 #ifdef serial
1269     ! copy the data without halo into the whole physical vector
1270     DO i = start_i, endl_i - 1
1271         DO j = start_j, endl_j - 1
1272             whole_v2(i, j) = v2(SIDX((i - start_i + 1), (j - start_j + 1)))
1273         END DO
1274     END DO

```

15/17

Freitag März 10, 2006

1467